

RECEIVED  
CENTRAL FAX CENTER

JUL 31 2007

In the Claims:

Kindly amend the claims as follows:

1 - 6 (Cancelled)

7. (Currently Amended) Grinding wheel including a circular wheel that rotates about a central axis and with a surface to which edge parts of a number of sand paper items are fastened, wherein the surface has increasing height inwards from a periphery of the surface, wherein the sand paper items have approximately the same height and are mounted mainly perpendicularly to the surface of the wheel and have approximately radial extension over the greater part of the radius of the surface, wherein the sand paper items ~~are chosen among sand paper items which~~ are slit inwards towards the surface ~~or sand paper items which consist of a number of sand paper strips.~~ and wherein the sand paper items are support by a number of brushes that are also mounted mainly perpendicularly to the surface of the wheel.

8. (Cancelled).

9. (Previously Presented) Grinding wheel according to claim 7, wherein the sand paper items are adapted to be exchanged individually.

10. (Currently Amended) Grinding wheel according to claim 8 7, wherein the support brushes are adapted to be exchanged individually.

11. (Currently Amended) Grinding wheel according to claim 8 7, wherein the sand paper items and the support brushes are adapted to be exchanged individually.

12. (Previously Presented) Grinding wheel according to claim 11, wherein the sand paper items and the support brushes are secured in a common foot.

13. (Previously Presented) Grinding wheel according to claim 7, wherein the

sand paper items are fastened in a radial groove in the surface of the grinding wheel.

14. (Currently Amended) Grinding wheel according to claim 8 7, wherein the sand paper items are fastened in a radial groove in the surface of the grinding wheel and the support brushes are fastened in holes in the surface of the grinding wheel.

15. (Previously Presented) Grinding wheel according to claim 7, wherein in order to ensure that the sand paper items cannot be flung out of the groove, the surface of the grinding wheel is designed with a locking means.

16. Cancelled